



ITEM	PART NUMBER		DESCRIPTION	QTY.
1	NPN	*	STANDARD #42 SPINDLE	1
2	NPN	*	STANDARD BRAKE FLANGE	1
3	CMB-133-8A		KODIAK CALIPER MOUNTING BRACKET	1
4	NPN	*	1/2-20UNF x 1 1/4 HEX BOLT	4
5	NPN	*	1/2-20UNF HEX NUT	4
6	NPN	*	1/2 LOCKWASHER	4
7	ROTOR HUB-133-8-10		KODIAK 13.3" HUB/ROTOR (8 ON 6 1/2")	1
8	LB3.165		KODIAK 5/8-18UNF LUG STUDS	8
9	02475	*	OUTER BEARING CONE	1
10	02420		OUTER BEARING CUP	1
11	25580	*	INNER BEARING CONE	1
12	25520		INNER BEARING CUP	1
13	472920 (NATIONAL)	*	SEAL	1
14	NPN	*	SPINDLE WASHER	1
15	NPN	*	SPINDLE NUT	1
16	ROTOR/HUB-8-PCAP		DUSTCAP	1
17	Q-10K RUBBER PLUG		DUSTCAP PLUG	1
18	DBC-250		KODIAK 250 CALIPER (LOADED)	1
19	DBC-MHBS		CALIPER SS GUIDE BOLT SLEEVE	2
20	DBC-MHGB		CALIPER SS GUIDE BOLT M11 x 1.5	2

\* NOT INCLUDED

NOTE: On air ride suspensions, Kodiak recommends "clocking" calipers as close to the lowest amplitude point as possible on the wheel end assembly.



7600 SAND STREET  
 FORT WORTH, TX 76118  
 PHONE 817-284-2324  
 FAX 817-595-2643  
 www.kodiaktrailer.com  
 Email: kodiak@kodiaktrailer.com

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KODIAK TRAILER COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KODIAK TRAILER COMPONENTS IS PROHIBITED. PROPRIETARY AND CONFIDENTIAL

UNLESS OTHERWISE SPECIFIED:  
 DIMENSIONS ARE IN INCHES  
 TOLERANCES:  
 FRACTIONAL: ± 1/64"  
 ANGULAR: MACH ± .5 DEG.  
 BEND ± 1 DEG.  
 TWO PLACE DECIMAL ± .01  
 THREE PLACE DECIMAL ± .005

DATE  
 12/08/2012  
 REVISION  
 12/10/2012

**HRCM-133-8A-10**  
**EXPLODED VIEW**