



4.88 HUB FACE TO BRAKE FLANGE

3.15 INNER BEARING SHOULDER TO BRAKE FLANGE

SECTION A-A

NOTE: On air ride suspensions, Kodiak recommends "clocking" calipers as close to the lowest amplitude point as possible on the wheel end assembly.



7600 SAND STREET  
 FORT WORTH, TX 76118  
 PHONE 817-284-2324  
 FAX 817-595-2643  
 www.kodiaktrailer.com  
 Email: kodiak@kodiaktrailer.com

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KODIAK TRAILER COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KODIAK TRAILER COMPONENTS IS PROHIBITED.  
 PROPRIETARY AND CONFIDENTIAL

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES  
 TOLERANCES:  
 FRACTIONAL: 1/64"  
 ANGULAR: MACH ± .5 DEG.  
 BEND ± 1 DEG.  
 TWO PLACE DECIMAL ± .01  
 THREE PLACE DECIMAL ± .005

DATE	REVISION
12/08/2012	
12/08/2012	

©

**HRCM-133-8D-9**  
**SECTION VIEW**