



| ITEM | PART NUMBER | | DESCRIPTION | QTY. |
|------|-------------------|---|---------------------------------------|------|
| 1 | NPN | * | STANDARD #42 SPINDLE | 1 |
| 2 | NPN | * | STANDARD 7K BRAKE FLANGE | 1 |
| 3 | NPN | * | STANDARD IDLER HUB (8 ON 6 1/2" B.C.) | 1 |
| 4 | LB3.165 | * | 5/8-18UNF LUG STUDS | 8 |
| 5 | 14125A | * | OUTER BEARING CONE | 1 |
| 6 | 14276 | * | OUTER BEARING CUP | 1 |
| 7 | 25580 | * | INNER BEARISNG CONE | 1 |
| 8 | 25520 | * | INNER BEARING CUP | 1 |
| 9 | 472920 (NATIONAL) | * | SEAL | 1 |
| 10 | NPN | * | SPINDLE WASHER | 1 |
| 11 | NPN | * | SPINDLE NUT | 1 |
| 12 | NPN | * | DUSTCAP | 1 |
| 13 | CMB-133-7 | | KODIAK CALIPER BRACKET | 1 |
| 14 | NPN | * | 3/8-16UNC x 1.00 HEX BOLT | 5 |
| 15 | NPN | * | 3/8-16UNC HEX NUT | 5 |
| 16 | ROTOR-133-7-10 | | KODIAK 13.3" ROTOR | 1 |
| 17 | DBC-250 | | KODIAK 250 CALIPER (LOADED) | 1 |
| 18 | DBC-MHBS | | CALIPER SS GUIDE BOLT SLEEVE | 2 |
| 19 | DBC-MHGB | | CALIPER SS GUIDE BOLT M11 x 1.5 | 2 |

* NOT INCLUDED

NOTE: On air ride suspensions, Kodiak recommends "clocking" calipers as close to the lowest amplitude point as possible on the wheel end assembly.



7600 SAND STREET
FORT WORTH, TX 76118
PHONE 817-284-2324
FAX 817-595-2643
www.kodiaktrailer.com
Email: kodiak@kodiaktrailer.com

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KODIAK TRAILER COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KODIAK TRAILER COMPONENTS IS PROHIBITED. PROPRIETARY AND CONFIDENTIAL

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL: 1/64"
ANGULAR: MACH ± .5 DEG.
BEND ± 1 DEG.
TWO PLACE DECIMAL ± .01
THREE PLACE DECIMAL ± .005

DATE

12/07/2012

REVISION

12/10/2012

©

**RCM-133-7-10
EXPLODED VIEW**