



ITEM	PART NUMBER		DESCRIPTION	QTY.
1	NPN	*	STANDARD #42 SPINDLE	1
2	NPN	*	STANDARD 7K BRAKE FLANGE	1
3	NPN	*	STANDARD IDLER HUB (8 ON 6 1/2" B.C.)	1
4	LB2.5	*	9/16-18UNF LUG STUDS	8
5	14125A	*	OUTER BEARING CONE	1
6	14276	*	OUTER BEARING CUP	1
7	25580	*	INNER BEARING CONE	1
8	25520	*	INNER BEARING CUP	1
9	472920 (NATIONAL)	*	SEAL	1
10	NPN	*	SPINDLE WASHER	1
11	NPN	*	SPINDLE NUT	1
12	NPN	*	DUSTCAP	1
13	CMB-133-7		KODIAK CALIPER BRACKET	1
14	NPN	*	3/8-16UNC x 1.00 HEX BOLT	5
15	NPN	*	3/8-16UNC HEX NUT	5
16	ROTOR-133-7-9		KODIAK 13.3" ROTOR	1
17	DBC-250		KODIAK 250 CALIPER (LOADED)	1
18	DBC-MHBS		CALIPER SS GUIDE BOLT SLEEVE	2
19	DBC-MHGB		CALIPER SS GUIDE BOLT M11 x 1.5	2

* NOT INCLUDED

NOTE: On air ride suspensions, Kodiak recommends "clocking" calipers as close to the lowest amplitude point as possible on the wheel end assembly.



7600 SAND STREET
 FORT WORTH, TX 76118
 PHONE 817-284-2324
 FAX 817-595-2643
 www.kodiaktrailer.com
 Email: kodiak@kodiaktrailer.com

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KODIAK TRAILER COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KODIAK TRAILER COMPONENTS IS PROHIBITED. PROPRIETARY AND CONFIDENTIAL

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL: 1/64"
 ANGULAR: MACH ± .5 DEG.
 BEND ± 1 DEG.
 TWO PLACE DECIMAL ± .01
 THREE PLACE DECIMAL ± .005

DATE

12/07/2012

REVISION

12/10/2012

©

**RCM-133-7-9
 EXPLODED VIEW**