



WELDED FLANGE ONLY  
WILL NOT FIT ON FORGED FLANGES  
CORNERS MITERED  
AT LEAST .25" FOR CALIPER FIT

ITEM	PART NUMBER	DESCRIPTION	QTY.
1	BT-16 SPINDLE	* 2K SPINDLE	1
2	BRAKE FLANGE	* 2K BRAKE FLANGE (WELD-ON ONLY)	
3	CMB-8-2B	KODIAK CALIPER MOUNTING BRACKET	1
4	7/16X1UNC BOLT	* BRACKET MOUNTING BOLTS	4
5	7/16UNC NUT	* BRACKET MOUNTING LOCKNUTS	4
6	HUB SPACER BT-16E	KODIAK HUB SPACER BT-16E (5 ON 4 1/2" B.C.)	1
7	LB169	KODIAK 1/2-120UNF LUG STUDS	5
8	L44649	* INNER & OUTER BEARING CONES	2
9	L44610	INNER & OUTER BEARING CUPS	2
10	BT SEAL (NATIONAL)	SEAL	1
11	ROTOR-8-2	KODIAK ROTOR-8-2	1
12	HUB SPACER -BT-16-BOLT	LOW PROFILE 3/8-16x1 HEX BOLT	5
13	SPINDLE_WASHER	* STANDARD AXLE HARDWARE	1
14	SPINDLE_NUT	* STANDARD AXLE HARDWARE	1
15	DUSTCAP	* STANDARD AXLE HARDWARE	1
16	DBC 225SB	KODIAK 225SB CALIPER (LOADED)	1
17	DBC-MHBS	KODIAK SS GUIDE SLEEVE	
18	DBC-MHGB	KODIAK SS GUIDE BOLT	

\* NOT INCLUDED



7600 SAND STREET  
FORT WORTH, TX 76118  
PHONE 817-284-2324  
FAX 817-595-2643  
www.kodiaktrailer.com  
Email: kodiak@kodiaktrailer.com

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KODIAK TRAILER COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KODIAK TRAILER COMPONENTS IS PROHIBITED. PROPRIETARY AND CONFIDENTIAL

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL: 1/64"  
ANGULAR: MACH ± .5 DEG.  
BEND ± 1 DEG.  
TWO PLACE DECIMAL ± .01  
THREE PLACE DECIMAL ± .005

DATE	REVISION
07/11/2012	
12/10/2012	

C

# RCMHS-8-2 EXPLODED VIEW